



Pharmacy Refrigerator with Freezer



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

Australia Headquarters

21b Lawler Drive, Oran Park, NSW,
2570, Australia
info@darsunscientific.com
+61-283135514, 430583632

DarsunScientific



Darsun Scientific Pharmacy Refrigerator with Freezer

DS-320



Product Overview

Microcomputer control, double display of refrigeration and freezing temperature.
Freezing and refrigeration double frequency conversion compressor system, independent control of refrigeration and freezing.
Optimization of refrigeration technology, better refrigeration capacity.
Hydrocarbon refrigerant, frequency conversion compressor, more energy saving and environmental protection.
Air-cooled design of refrigerating chamber ensures constant temperature.
Freezing temperature: -10°C ~ -40°C, refrigeration temperature: 2°C ~ 8°C.

Product Features

Multiple alarm functions: it can realize high and low temperature alarm, sensor fault alarm and refrigerator door opening alarm.
Two alarm modes: sound buzzer alarm and digital flashing alarm.
Multiple protection functions: startup delay and shutdown interval.

CONSTRUCTION & SPECIFICATION:-

- Double Door Deep Freezer cum Refrigerator Compact Vertical model.
- Energy Efficient. Ultra low power consumption.
- Robust double walled construction, quality material with tight tolerances
- Outer front double walled lockable double doors are insulated and are fitted with magnetic tape for air tight closing for no temperature loss, provided with separate lock and key arrangement.
- Rigid High grade PUF INSULATION between outer and inner chamber for minimal thermal losses.
- Each chamber has a separate Outer door to minimize the loss of temperature. Direct cooling system inside the chamber
- Audible/Visual Alarms for High-Low Temperature, Door Ajar, Power failure, Low Battery.
- Mounted of heavy duty lockable caster wheels (04 Nos) for easy portability.
- Supplied with cord and plug. Operating Voltage: 220-240 Volts, 50/60 Hz Single Phase

Model	DS-320
Refrigeration temperature (°C)	2 ~ 8
Voltage/Frequency (V/Hz)	220 / 50
Power (W)	320
Effective volume (L)	320
Net weight (Kg)	146
Freezing temperature (°C)	-10 ~ -40
External dimension (mm)	765x811x1873