



VERTICAL STEAM STERILIZER



Darsun Scientific Inc, USA
30N Gould St Ste R Sheridan, Wyoming
82801, United States

Email: Info@darsunscientificinc.com
Phone: +1-3074272810
Web: www.darsunscientificinc.com

DarsunScientific



Darsun Scientific

VERTICAL STEAM STERILIZER

DSL-G



Product Overview

Suitable for laboratories in industrial and mining enterprises, colleges and universities ,medical and health units etc., for culture experiments of microorganisms and bacterial.

Product Features

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters.
- Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With drying function
- With automatic protection function over temperature protection; over pressure protection; low water level protection; anti dry burning .
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop.
- Automatic discharge of cold air, automatic steam exhaust after sterilization.
- **Optional external printer**
- **Optional automatic water**

Model	DSL-35G	DSL-50G	DSL-75G	DSL-100G
Volume	35 L	50 L	75 L	100 L
Power	3.5 KW	3.5 KW	4.5 KW	4.5 KW
Voltage	AC 220 V, 50 HZ			
Design Pressure	0.25MPa			
Rated working pressure	0.22 Mpa			
Rated working temperature	134 °C			
Sterilization temperature	50°C - 134 °C			
Sterilization time setting range	4 - 120 min			
Drying time setting range	0 - 240 min			
Chamber volume (mm)	0 350 x 400	0 350 x 525	0 400 x 625	0 450 x 650
Bucket dimension (mm)	0 330 x 320	0 330 x 460	0 380 x 560	0 420 x 540
Basket dimension (optional)	0 320 x 350	0 320 x 240 x 2	0 360 x 280 x 2	0 410 x 300 x 2
Outer dimension (mm)	498 x 498 x 940	498 x 498 x 1110	570 x 570 x 1185	588 x 588 x 1255
Packing size (L x W x H)(mm)	580 x 630 x 1130	580 x 630 x 1230	630 x 680 x 1290	690 x 650 x 1410
Gross / Net weight	79 / 581%	106 / 80 kg	120 / 90 kg	133 / 106 kg