



DB

Mini Dry Bath



Darsun Scientific Inc, USA
503 N Gould St, Ste R, Sheridan, Wyoming
82801, United States

Email : info@darsunscientific.com
Phone : +1-3078722810
Web : www.darsunscientific.com

DarsunScientific



Darsun Scientific

Mini Dry Bath

DS-MDB100C/DS-MDB100



FEATURES



Multi-point operation



Small volume



Over temperature protection



LCD display

Model	DS-MDB100C	DS-MDB100
Temperature Range	Room temp - 15°C ~ 100°C	Room temp + 5°C ~ 100°C
Temperature Stability	±0.5°C	±0.5°C
Temperature Homogeneity	±0.5°C	±0.5°C
Display Accuracy	0.1°C	0.1°C
Heating Time	≤12min (25-100°C)	≤12min (25-100°C)
Cooling Time	20 - 25 min (20-0°C)	/
Multi-point Operation	Yes	No
Temperature Point Can Be Set	9	9
Time Setting Range	5s - 23h59min	5s - 23h59min
Power	60W	48W
Voltage	AC100-240V	AC100-240V
Size	160*115*96 mm	160*115*96 mm

Module Options	Numbers And Aperture Of Test Tube
MDB1	40 * 0.2ml Centrifuge tube
MDB2	24 * 0.5ml Centrifuge tube
MDB3	15 * 1.5ml Centrifuge tube
MDB4	15 * 2.0ml Centrifuge tube
OEM Of Modules	Modules can be customized according to customer needs