



TM

Turbidity Meter



Darsun Scientific Inc, USA
30N Gould St Ste R Sheridan, Wyoming
82801, United States

Email: Info@darsunscientificinc.com
Phone: +1-3074272810
Web: www.darsunscientificinc.com

DarsunScientific

Darsun Scientific

Turbidity Meter

DSTU200P



GENERAL FEATURES

- 850nm LED light Source.
- Uses Nephelometric principle with 90° detection.
- Meets ISO 7027 and offers consistent light source for higher accuracy.
- Selectable turbidity units, including the NTU, FNU and EBC.
- Settable parameters, including user ID, number of calibration points, data and time, etc.
- Auto-power-off feature effectively extends the battery usage time.
- IP65 waterproof. The portable meter is suitable for fields measurements and out door measurements.
- 1-3 points calibration using Formazin standards or zero water.
- Autoranging from 0-200 NTU.

INCLUDES

- 5 pcs turbidity bottles
- Carrying Case

Model	DSTU200P	
Measuring Unit	Range	(0~20.00) NTU, (20.0~200.0) NTU
	Resolution	0.01NTU, 0.1NTU, 1NTU
	Accuracy	±2% of reading+0.02NTU
	Repeatability	≤1.0%
	Fluctuation	±1.0% FS/30min
General	Power Supply	AA Battery, AC Adapter, 200~240 VAC input, DC 5V output
	Dimensions	100×220×80 mm
	Net Weight	0.8 kg
	Dimensions (Carton)	300×290×140 mm
	Shipping Weight	5 kg