



CM

Conductivity Meter



Darsun Scientific Inc, USA
30N Gould St Ste R Sheridan, Wyoming
82801, United States

Email: Info@darsunscientificinc.com

Phone: +1-3074272810

Web: www.darsunscientificinc.com

DarsunScientific



Darsun Scientific

Conductivity Meter

DSEC110B

DJS-1VC EC electrode
1413 $\mu\text{S}/\text{cm}$ EC standard solution, 50ml, 1 vial
Electrode holder
Silicone rubber case
Wristbands



LCD display screen, 3.5 inches.

Reset feature automatically resumes all settings back to factory default options.
Auto-power off feature effectively extends the battery service life.

IP65 waterproof. The portable meter is suitable for fields measurements and out door measurements.

Cell constant is settable

Manual temperature compensation ensures accurate results.

Model		DSEC110B
Parameters		EC
Conductivity	Range	0.00 $\mu\text{S}/\text{cm}$ to 100 mS/cm
	Resolution	0.01 $\mu\text{S}/\text{cm}$ minimum, various with range selection
	Accuracy	$\pm 1.0\%$ FS
	Reference Temperature	25 $^{\circ}\text{C}$
Measurement	Reading Mode	Continuous
	Reading Prompts	Reading, Stable
	Temp. Compensation	MTC
Inputs	Conductivity	5-pin aviation connector
Display options	Backlight	Yes
	Auto Shutdown	300, 600, 1200, 1800, 3600 sec., off
	IP Rating	IP65
General	Power	Rechargeable Lithium battery, AC Adapter, 100-240V AC input, DC5V output
	Dimensions	80×225×35 mm
	Net Weight	400g (0.88 lb)
	Dimensions (Carton)	300×290×140 mm
	Shipping Weight	1 kg