




PH pH Meter



Darsun Scientific Inc, USA
30N Gould St Ste R Sheridan, Wyoming
82801, United States

Email: Info@darsunscientificinc.com

Phone: +1-3074272810

Web: www.darsunscientificinc.com

DarsunScientific



Darsun Scientific

pH Meter 300F



E-301-QC 3 in 1 pH composite electrode
NIST pH standard solution(4.01, 7.00,
10.01) , 50ml/vial
REX-5 electrode stand

- High resolution LCD display, 5.7 inches.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 500 sets (GLP-compliant).
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.
- 1-5 points calibration with Standard Recognition.
- Selectable pH buffer groups, including NIST, DIN, GB, USA.
- Automatic electrode diagnosis with pH slope and offset display.

Model Parameters		DS300F
pH	Range	pH/Temp.(mV) -2.00 to 20.00pH
	Resolution	0.1, 0.01 pH
	Accuracy	±0.01 pH
	Calibration Points	Up to 5
	Standard Customization	Yes
	Standard Recognition	NIST, GB, USA and DIN buffers
mV	Range	-2000.0 to 2000.0 mV
	Resolution	0.1 mV
	Accuracy	±0.3 mV or ±0.1%
Temperature	Range	-5 to 110 °C, 23 to 230 °F
	Unit	°C, °F
	Resolution	0.1
Measurement	Accuracy	±0.2°C
	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Locked
Data management	Temp. Compensation	ATC, MTC
	Data Storage	500 results each
	GLP Features	Yes
Inputs	pH Electrode	BNC(Q9)
	Temp. Probe	4-pin aviation connector
Outputs	USB	PC
	RS 232	printer
Display options	Backlight	Yes
	Auto Shutdown	1~60 min, off
	IP Rating	IP54
General	Date and Time	Yes
	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242×195× 68 mm
	Net Weight	900g (1.98 lb)
	Dimensions (Carton)	370×320×220 mm
	Shipping Weight	2.5 kg