



High-Temperature Aging Chamber



Darsun Scientific Inc, USA
30N Gould St Ste R Sheridan, Wyoming
82801, United States

Email: Info@darsunscientificinc.com
Phone: +1-3074272810
Web: www.darsunscientificinc.com

DarsunScientific

Darsun Scientific

High-Temperature Aging Chamber

DSR-15m³



Product Overview

Can set 8 groups of TMER time values;
Simple and user-friendly human-machine interface;
Equipped with AUTO RESET function;
10A load capacity, with electromagnetic switch to drive large loads;
End-of-execution alarm, can be connected to an external BUZZER or light signal for notification;
Data can be stored and will not disappear after power OFF.

Model	DSR-15m ³
Temperature range	Room Temp.+20 to +100℃
Control accuracy	±0.5℃
Uniformity	3℃
Internal dimensions (mm)	W1400×D1200×H1800
External dimensions (mm)	W1950 ×D2750×H2200
Test capacity	88PCS/CYCLE(or customized by customer)
Sample dimensions(mm)	100W*100H*50D
Detection range	Full FAN quantity
Voltage range	3 to 50V
Current range	±5%
Rotation speed	0 to 15000RPM,±8%
Detection speed	7 to 12sec/cycle

Product Features

Isolated Aging Chamber Features

- Product area and load area are isolated with a split-type load for easy maintenance and temperature control
- Temperature range: 40 to 70°C $\pm$ 3/ $\pm$ 5°C
- Accuracy: $\pm$ 0.5°C
- Temperature uniformity: 5°C&3°C
- Test rack material: Painted or formed aluminum combination.
- Insulation: PU foam (door with double-layer glass) for thermal insulation, ensuring internal temperature is not affected by external factors, achieving energy-saving effects.
- Products are placed in layers, with layer height adjustable as required for easy access. Can be equipped with a computer monitoring system as per customer requirements.
- Noise controls $\leq$ 75dB

Integrated Aging Chamber Features

- Combined isolation, PD & closed-loop temperature control.
- Temperature range: 40 to 70°C $\pm$ 3/ $\pm$ 5°C
- Temperature uniformity: 5°C&3°C
- Insulation: PU foam (door with double-layer glass) for thermal insulation, ensuring internal temperature is not affected by external factors, achieving energy-saving effects.
- Burn-in Trolley:
 - Convenient for painted/formed aluminum/stainless steel welded trolleys. Layer height and width are customized according to customer requirements for easy access.
 - Trolleys can be easily pushed in and out, facilitating product loading and unloading, and equipment maintenance.
- Can be equipped with a computer monitoring system as per customer requirements.
- Noise controls $\leq$ 75dB

